REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB

PLEASE DO NOT RETURN YOUR FO	RM TO TH	E ABOVE ORGANIZATION	ON.			
1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE				3. DATES COVERED (From - To)		
31MAR2010	Final			01JUL 2004 to 31DEC 2009		
4. TITLE AND SUBTITLE				5a. CON	NTRACT NUMBER	
(MURI-04) CONFORMAL ANTENNA ANALYSIS AND DESIGN USING						
NOVEL ELECTRONIC MATERIALS				5b. GRANT NUMBER		
				JD. GRA	FA9550-04-1-0359	
				FA9550-04-1-0559		
				5c. PRO	GRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER		
John L. Volakis				Control of the Contro		
nemages in Annie en 8073 (165000 77)						
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
				la i		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)					8. PERFORMING ORGANIZATION REPORT NUMBER	
THE OHIO STATE UNIV/OFFICE OF SPONSORED PROGRAMS					REPORT NOMBER	
1960 KENNY ROAD						
COLUMBUS, OH 43210						
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				10. SPONSON/MONTON S ACRONTINGS		
AF OFFICE OF SCIENTIFIC RESEARCH 875 NORTH RANDOLPH STREET ROOM 3112						
ARLINGTON VA 22203				4	11. SPONSOR/MONITOR'S REPORT	
ARDINGTON VA 22203					NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT						
UNLIMITED						
WATMAATAA A MAY						
13. SUPPLEMENTARY NOTES						
14. ABSTRACT						
THE OBJECTIVE OF THIS ADDITIONAL WORK EFFORT IS TO PROVIDE THE CONCEPTUAL FOUNDATIONS FOR						
DESIGNING MINIATURE ANTENNAS HAVING GREATER MODE DIVERSITY FNA BANDWIDTH BY THE						
INCORPORATION OF MAGNETIC MATERIALS. THE PI AND A GRAUDATE STUDENT WILL EXPLORE THE						
INCORPORATION OF CERTAIN MAGNETIC MATERIALS (PARTICULARYLY METAFERRITES) IN THE ANTENNA						
SUBSTRATE. THEY WILL ALSO EXPLORE THE POSSIBLE MONRECIPROCAL BEHAVIOR THE SUCH MATERIALS						
MIGHT EXHIBIT. THE AF ANTICIPATES FIELDING SMALLER AND MORE AGILE ANTENNAS ON ITS EXPANDING						
FLEET OF UAVS AND THE RESEARCH PURSUED HERE WILL SPEAK TO THAT GOAL.						
15. SUBJECT TERMS						
					ME OF RESPONSIBLE PERSON	
a. REPORT b. ABSTRACT c. Th	HIS PAGE ABSTRAC	ABSTRACT	OF PAGES	The Association III and	Volakis	
				19b. TEL	19b. TELEPHONE NUMBER (Include area code)	

AFOSR MURI Transition Projects

Conformal Antenna and Array Design Using Novel Electronic Materials: FA 9550-04-1-0359

This MURI was about the invention/discovery, analysis, demonstration and realization of novel propagation modes that led to extremely slow waves (as photonic crystal modes) in textured layered dielectric (metamaterials). Of importance is these modes are nonthat reflecting the air-dielectric at interfaces. As a result. efficiency of the receiving or transmitting antennas based on these modes is extremely high, even though the antenna structure is very small.

A key discovery during the course of the MURI was the realization of such anisotropic media in a planar configuration using simple printed microstrip lines (coupled lines, possibly loaded with lumped elements such as capacitors and inductors, see Fig. 1). This discovery led to many new and easy to manufacture miniature antennas. Because of their very low cost, order of magnitude in size reduction, and conformal nature, these antennas are finding transition in many ubiquitous applications.

It is well known that the inclusion of low loss ferrites within the substrate of the printed coupled lines will significantly enhance bandwidth and radiation. A concept that includes ferrite inserts printed structures is depicted in Fig. 2. Currently, we are examining modes that can be realized using these structures to motivated




Fig. 1. Volumetric anisotropic media with corresponding equivalent printed circuits having the same properties (using low cost uniform substrates). This patented technology was developed under the AFSOR MURI, and is the most promising for transformational impact on all aspects of RF/EO applications




Fig. 2. Top: Artificially realized nisotropic media exhibiting novel phenomena using low cost layered coupled lines, with possible ferrite inserts for mode diversity and bandwidth increase. **Bottom:** Printing on low loss hexaferrite (BaM) fabricated at Ohio State using uniform small platelets, formed as low as 700° C, by Pechini method. Due to demag., it is necessary to use ferrites with low $4\pi M_s$ (500-600G) to assure saturation. These ferrite layers can be used with the coupled transmission lines to realize a diversity of modes, and more importantly bandwidth.

future research in developing low loss magnetic materials. An example of low loss ferrites with aligned platelets via the Pechini method is also depicted in Fig 2.

Two example transition projects were recently awarded by AFRL to exploit the smaller antennas and arrays that can be realized using the low cost metamaterials developed under the referenced AFOSR. They are

AFRL Contract No. FA8650-09-C-1656

Award to *Lockheed Martin Corp*. (Skunk Works, Palmdale, CA, charles.chase@lmco.com) in Oct 2009 with subcontract to Ohio State. Phase I: 9 months (Phase II is subject to progress and review in May 2010)

Title: *Metamaterials for RF Applications*

This project exploits the much smaller developed metamaterial antenna elements (at least 5 times smaller) to realize wideband metamaterial arrays. As is well known, array elements must be no more than $\lambda/2$ apart (center to center) to suppress potential grating lobes. This limits the possibilities of designing wideband arrays. However, if the antenna element is $\lambda/4$ in length at f_L and still resonate, the array can potentially achieve a 2:1 bandwidth (one octave) as the element to element separation will be $\lambda/2$ when the frequency reaches $f_U=2f_L$. Correspondingly, as the new MURI antenna elements are $\lambda/10$ in size, the potential array bandwidth can be a remarkable 5:1. Coupling between multiple elements allows for even lower resonances when the individual elements are only $\lambda/20$ in size, implying a 10:1 array bandwidth.




Figure 3. Miniature ultrawideband aperture formed by interconnected metamaterial antenna elements. The latter were developed under the MURI program and were interconnected to form small wideband metamaterial arrays. Remarkably, as much as 10:1 and 20:1 bandwidths have been theoretically demonstrated for conformal apertures by exploiting the current sheet realization introduced by the late Ben Munk at the Ohio State Univ. (building on previous concepts introduced by Wheeler)

Under this AFRL transition project, Ohio State is helping LMC develop a reduced size FOPEN (foliage penetration) array. Current FOPEN is large and heavy, and must be installed as an appendage below the airborne vehicle. Under this effort, the array will be reduced in size by at least a factor of 2 per linear dimension. More importantly, it will be designed for conformal installations using the concepts outlined in Fig. 3.

AFRL Contract No. FA8650-09-C-1658

Award to *Boeing Corp.* (Seattle, WA, grant.e.davis@boeing.com) in Oct 2009 with subcontract to Ohio State. Phase I: 9 months (Phase II is subject to progress and review in May 2010) **Title:** *Metamaterials Broadband Direction Finding Antenna Development*

The aim of this project is to replace current blade antenna that are highly protruding and impede airframe take-off (retracted during take-off to avoid being damaged). Currently, 3 blade antennas are used to cover the band of 30-500MHz for direction finding purposes. The newly proposed antenna is a miniature spiral incorporating volumetric coiling for size reduction that nearly reaches the optimal limits. To retain its performance in conformal installations, a metamaterial ground plane, constructed from textured, substrates will be adapted as depicted in Fig. 4.




Figure 4. Miniature conformal spirals on textured/metamaterial ferrite substrates (middle) to replace traditional blade antennas that protrude nearly 1meter above the airframes surface, and require retraction for take-off. New antenna will be only 3"-4" in height, and will replace 3 separate 1meter tall blades needed to cover the entire band of 30-500MHz.